

JM3 30~370kg load range, 15mm deflection.

Features

JM3 spring vibration mount is mainly composed of a rubber gland, a steel shell, an adjustable bolt and a vibration isolation spring. The gland is a combination of rubber and steel plate, which can effectively prevent noise caused by collision and friction.

The product is designed with transportation fixing bolts on both sides for easy installation. Tightening the protective bolts on both sides before transportation can effectively prevent damage to the equipment components caused by transportation vibration and shaking.



Technical Data

Type	Model No.	Technical Data				Installation Dimensions (±2mm)					
		Load (kg)	Load (Lbs)	Deformation (mm)	Vertical Rigidity (kg/mm)	L	W	H	C	D	S
JM3	30	30	66	10~15	2.00	139	84	105	102	13	M16x80
	40	40	88	10~15	2.67						
	60	60	132	10~15	4.00						
	80	80	176	10~15	5.33						
	100	100	220	10~15	6.67						
	120	120	265	10~15	8.00						
	140	140	309	10~15	9.33						
	170	170	375	10~15	11.33						
	200	200	441	10~15	13.33						
	230	230	507	10~15	15.33						
	280	280	617	10~15	18.67						
	320	320	705	10~15	21.33						
370	307	816	10~15	24.67							

